



iQ300
LC96BBM50
LC96BBM50 stainless steel
Chimney hood, 90 cm
Box design



Optional accessories

LZ57000	cleanAir Recirculation Kit
LZ56200	CleanAir active carbon filter spare part
LZ50961	Backboard 90 x 72 cm
LZ50960	Backboard 90x65cm
LZ12350	Chimney extension 1500 mm
LZ12250	Chimney extension 1000 mm
LZ10FXJ00	Integrated CleanAir Recirculation Kit
LZ10FXI00	Integrated CleanAir Recirculation Kit
LZ10DXU00	Recirculating kit
LZ10DXA00	Active carbon filter
LZ00XXP00	CleanAir act.carbon filter regenerative

Extractor hood in Box design with high extraction rate.

- ✓ The powerful motor with an high extraction rate of 580 m³/h for fresh air in your kitchen.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ At 60 dB the hood is pleasantly quiet when being used.
- ✓ The intensive setting temporarily increases the extraction rate when kitchen vapour is especially intense, with automatic revert after 6 min.
- ✓ Thanks to touchControl the power level and the LED light can be selected directly.

Features

Technical Data

Color chimney : Stainless steel
 Typology : Chimney
 Approval certificates : CE, Eurasian, Ukraine, VDE
 Length electrical supply cord (cm) : 130
 Height of the chimney (mm) : 583-912/583-1022
 Height of product, without chimney (mm) : 53
 Net weight (kg) : 12.377
 Type of control : Electronic
 Maximum output air extraction (m³/h) : 360
 Boost position output recirculating (m³/h) : 350
 Maximum output recirculating air (m³/h) : 280
 Boost position air extraction (m³/h) : 580
 Number of lights : 2
 Noise level (dB) : 60
 Diameter of air outlet (mm) : 150 / 120
 Grease filter material : Washable aluminium
 Odour filter : No
 Operating Mode : Convertible
 Optional accessories : LZ00XXP00, LZ10DXA00, LZ10DXU00, LZ10FXI00, LZ10FXJ00, LZ12250, LZ12350, LZ50960, LZ50961, LZ56200, LZ57000
 Type of lamps used : LED
 Grease filter type : Kassette
 Connection Rating (W) : 220
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 50; 60
 Plug type : Gardy plug w/ earthing
 Installation typology : Wall-mounted
 Material body : Stainless steel
 Approval certificates : CE, Eurasian, Ukraine, VDE
 Plug type : Gardy plug w/ earthing
 Dimensions of the product, with chimney (if exists) (in) : / x x
 Dimensions of the packed product (in) : 18.89 x 25.59 x 40.55
 Net weight (lbs) : 27
 Gross weight (lbs) : 40
 Motor location : Integrated motor in hood chimney
 No-return airflow flap : Yes
 Length electrical supply cord (cm) : 130
 Dimensions of the product, with chimney (if exists) (mm) : 635-1075 MM x 900 x 500
 Dimensions of the packed product (HxWxD) (mm) : 480 x 650 x 1030
 Net weight (kg) : 12.377
 Gross weight (kg) : 18.0





iQ300 LC96BBM50 LC96BBM50 stainless steel Chimney hood, 90 cm Box design

Features

- Energy Efficiency Class: A (at a range of energy efficiency classes from A++ to E)
- Average Energy Consumption: 43.9 kWh/year
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A
- Grease Filtering Efficiency Class: D
- Noise min./max. Normal Level: 48/60 dB

Variant:

Design:

Operating and power:

Operating mode / operation

Power:

Environment and safety:

Comfort:

Measures:

Technical information:

- Chimney hood
- Appliance colour: stainless steel
- 90 cm Chimney hood
- 90 cm wide
- Suitable for ducted or re-circulated extraction
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Wall mounted hood
- touchControl for extractor speeds and light
- Electronic controls
- Electronic control via touch control
- touchControl with Electronic display
- 3 speeds plus intensive setting via touchControl
- Electronic controls via touchControl with Electronic display
- touchControl (3 speeds plus intensive setting) with Electronic display
- 3 speeds plus intensive setting
- Automatic revert setting, 6 minutes
- Twin channel high performance fan motor
- Energy efficient capacitor motor
- 2 x 1,5W LED
- Light Intensity: 221 lux
- Colour Temperature: 3500 K
- Metal grease filter, dishwasher safe
- Extraction rate according to EN 61591 \varnothing 15 cm:
 - max. Normal use 360 m³/h
 - Intensive 580 m³/h
- Extraction rate exhaust air according to EN 61591 max. 360 m³/h
- Maximum extraction rate exhaust air 360 m³/h according to EN 61591
- Extraction rate exhaust air according to EN 61591:
 - max. normal use 360 m³/h, intensive 580 m³/h
- Noise level according to EN 60704-3 und EN 60704-2-13 at max. normal use exhaust air: 60 dB(A) re 1 pW (48 dB(A) re 20 μ Pa sound pressure)

- Noise level according to EN 60704-3 und EN 60704-2-13 exhaust air:
 - Max. normal use: 60 dB(A) re 1 pW sound pressure:48 dB(A)
 - Intensive: 70 dB(A) re 1 pW (58 dB(A) re 20 μ Pa sound pressure)
 - Diameter pipe \varnothing 150 mm (\varnothing 120 mm enclosed)
 - with one-way flap
 - Max. extraction rate: 580 m³/h
 - Extraction rate in recirculation mode:
 - Max. normal use: 280 m³/h
 - Intensive: 350 m³/h
 - Noise levels in recirculation mode:
 - Max. normal use: 71 dB(A) re 1 pW (59 dB(A) re 20 μ Pa sound pressure)
 - Intensive: 75 dB(A) re 1 pW (63 dB(A) re 20 μ Pa sound pressure)
 - Dimensions exhaust air (HxWxD): 635-965 x 900 x 500 mm
 - Dimensions recirculating (HxWxD): 635-1075 x 900 x 500 mm
 - Dimensions recirculating with CleanAir module (HxWxD):
 - 703 x 900 x 500 mm - mounting with outer chimney
 - 833-1163 x 900 x 500 mm - mounting with telescopic chimney
 - Dimensions recirculating with cleanAir module (HxWxD):
 - 703 x 900 x 500 mm - mounting with outer chimney
 - 833-1163 x 900 x 500 mm - mounting with telescopic chimney
 - Dimensions recirculating with CleanAir module (HxWxD):
 - 703 x 900 x 500 mm - mounting with outer chimney
 - 833-1163 x 900 x 500 mm - mounting with telescopic chimney
 - Power rating: 220 W
 - Electrical cable length 1.3 m
- * In accordance with the EU-Regulation No 65/2014



iQ300
LC96BBM50
LC96BBM50 stainless steel
Chimney hood, 90 cm
Box design

Dimensioned drawings

