



Serie | 6

DIB97JP50 DIB97JP50 Brushed steel Island chimney hood Box design



A

The island chimney hood: the perfect solution for your cooking island thanks to flexible ceiling mounting.

- **EcoSilence Drive:** our highly efficient motor saves on energy, not on performance.
- **DirectSelect control:** direct selection of desired settings and light.
- **extra silent:** maximal extractor performance with very minimal noise.
- **Grease filtration level:** filters out up to 86.6% of the grease from kitchen air.

Technical Data

| | |
|---|----------------------------------|
| Color chimney : | Stainless steel |
| Typology : | Chimney |
| Approval certificates : | CE, VDE |
| Length electrical supply cord (cm) : | 130 |
| Height of the chimney (mm) : | 698-878/698-998 |
| Height of product, without chimney (mm) : | 46 |
| Net weight (kg) : | 32.057 |
| Type of control : | Electronic |
| Number of speed settings : | 3-stage + 2 intensive |
| Maximum output air extraction (m ³ /h) : | 445 |
| Boost position output recirculating (m ³ /h) : | 391 |
| Maximum output recirculating air (m ³ /h) : | 334 |
| Boost position air extraction (m ³ /h) : | 718 |
| Number of lights : | 4 |
| Noise level (dB) : | 54 |
| Diameter of air outlet (mm) : | 150 / 120 |
| Grease filter material : | Washable stainless steel |
| Odour filter : | No |
| Operating Mode : | Convertible |
| Delay Shut off modes : | 10M |
| Optional accessories : | |
| DHZ1231, DHZ1241, DHZ1246, DHZ1251, DHZ1253, DHZ1256, DHZ5346, DHZ5385, DSZ5201, DSZ6230, DZZ0XX0P0 | |
| Type of lamps used : | LED |
| Grease filter type : | Kassette |
| Connection Rating (W) : | 146 |
| Current (A) : | 10 |
| Voltage (V) : | 220-240 |
| Frequency (Hz) : | 50; 60 |
| Plug type : | Gardy plug w/ earthing |
| Installation typology : | Island |
| Material body : | Stainless steel |
| Approval certificates : | CE, VDE |
| Plug type : | Gardy plug w/ earthing |
| Dimensions of the product, with chimney (if exists) (in) : | / x x |
| Dimensions of the packed product (in) : | 33.07 x 24.01 x 40.94 |
| Net weight (lbs) : | 71 |
| Gross weight (lbs) : | 90 |
| Motor location : | Integrated motor in hood chimney |
| No-return airflow flap : | Yes |
| Length electrical supply cord (cm) : | 130 |
| Dimensions of the product, with chimney (if exists) (mm) : | 744-1044 x 898 x 600 |
| Dimensions of the packed product (HxWxD) (mm) : | 840 x 610 x 1040 |
| Net weight (kg) : | 32.057 |
| Gross weight (kg) : | 41.0 |

Optional accessories

- DHZ1231 : Adapter for roof inclination left/right
- DHZ1241 : Adapter for roof inclination front/back
- DHZ1246 : Chimney extension 1100 mm
- DHZ1251 : Extension for mounting kit 500 mm
- DHZ1253 : Extension for mounting kit 1000 mm
- DHZ1256 : Chimney extension 1600 mm
- DHZ5346 : Active carbon filter
- DHZ5385 : Recirculating kit
- DSZ5201 : CleanAir active carbon filter spare part
- DSZ6230 : CleanAir Recirculation Kit
- DZZ0XX0P0 : CleanAir act.carbon filter regenerative





Serie | 6 Hoods

DIB97JP50

DIB97JP50 Brushed steel

Island chimney hood

Box design

The island chimney hood: the perfect solution for your cooking island thanks to flexible ceiling mounting.

- Energy Efficiency Class: A (at a range of energy efficiency classes from A++ to E)
- Average Energy Consumption: 31.3 kWh/year
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A
- Grease Filtering Efficiency Class: B
- Noise min./max. Normal Level: 46/54 dB

Variant:

Design:

Operating and power:

Operating mode / operation

Power:

Environment and safety:

Comfort:

Measures:

Technical information:

- Island chimney hood
- 90 cm wide
- Appliance colour: Brushed steel
- Suitable for ducted or re-circulated extraction
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Ceiling mounted hood
- TouchControl for extractor speeds and light
- Electronic controls
- TouchControl with lightline
- 3 speeds plus 2 intensive via TouchControl
- Electronic controls via TouchControl with lightline
- TouchControl (3 speeds plus 2 intensive) with lightline
- 3 speeds plus 2 intensive
- Automatic revert setting, 6 minutes
- Automatic 10 minutes after running
- easy to clean Innerframe
- Light dimmer function
- SoftLight
- Efficient BLDC-technology
- 4 x 1,5W LED
- Light Intensity: 425 lux
- Colour Temperature: 3500 K
- Saturation indicator for metal and charcoal filter
- Stainless steel filter covers, dishwasher safe
- Metal grease filter, dishwasher safe
- Extraction rate according to EN 61591 \varnothing 15 cm:
max. Normal use 444 m³/h
Intensive 718 m³/h
- Extraction rate exhaust air according to EN 61591 max. 444 m³/h
- Maximum extraction rate exhaust air 444 m³/h according to EN 61591
- Extraction rate exhaust air according to EN 61591:
max. normal use 444 m³/h, intensive 718 m³/h
- Dimensions recirculating with CleanAir module (HxWxD):
812-1044 x 898 x 600 mm
- Additional noise insulation
- Noise level according to EN 60704-3 und EN 60704-2-13 at
max. normal use exhaust air: 54 dB(A) re 1 pW (41 dB(A) re 20 μ Pa sound pressure)
- Noise level according to EN 60704-3 und EN 60704-2-13
exhaust air:
Max. normal use: 54 dB(A) re 1 pW sound pressure: 41 dB(A)
Intensive: 65 dB(A) re 1 pW (52 dB(A) re 20 μ Pa sound pressure)
- Diameter pipe \varnothing 150 mm (\varnothing 120 mm enclosed)
- with one-way flap
- Max. extraction rate: 718 m³/h
- Extraction rate in recirculation mode:
Max. normal use: 334 m³/h
Intensive: 391 m³/h
- Noise levels in recirculation mode: 2/4
Max. normal use: 70 dB(A) re 1 pW (57 dB(A) re 20 μ Pa sound pressure)
Intensive: 74 dB(A) re 1 pW (61 dB(A) re 20 μ Pa sound





CMC
ELECTRIC



BOSCH

Serie | 6 Hoods

** In accordance with the EU-Regulation No 65/2014*



