

Serie | 6

DWB97JP50
DWB97JP50 Brushed steel
Chimney hood
Box design

A



The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.

- **EcoSilence Drive:** our highly efficient motor saves on energy, not on performance.
- **DirectSelect control:** direct selection of desired settings and light.
- **extra silent:** maximal extractor performance with very minimal noise.
- **Grease filtration level:** filters out up to 85.3% of the grease from kitchen air.

Technical Data

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Height of product, without chimney (mm) :	46
Net weight (kg) :	19.663
Type of control :	Electronic
Number of speed settings :	3-stage + 2 intensive
Maximum output air extraction (m3/h) :	427
Boost position output recirculating (m3/h) :	378
Maximum output recirculating air (m3/h) :	324
Boost position air extraction (m ³ /h) :	702
Number of lights :	3
Noise level (dB) :	55
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable stainless steel
Odour filter :	No
Operating Mode :	Convertible
Delay Shut off modes :	10M
Optional accessories :	DHZ1223, DHZ1233, DHZ5345, DHZ5346, DSZ5201, DSZ6240, DWZ0XX0J5, DWZ0XX0J5, DZZ0XX0P0, HEZG9AS00S
Type of lamps used :	LED
Grease filter type :	Kassette
Connection Rating (W) :	145
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	Gardy plug w/ earthing
Installation typology :	Wall-mounted
Material body :	Stainless steel
Approval certificates :	CE, VDE
Plug type :	Gardy plug w/ earthing
Dimensions of the product, with chimney (if exists) (in) :	/ x x
Dimensions of the packed product (in) :	22.83 x 25.59 x 38.18
Net weight (lbs) :	43
Gross weight (lbs) :	56
Motor location :	Integrated motor in hood chimney
No-return airflow flap :	Yes
Length electrical supply cord (cm) :	130
Dimensions of the product, with chimney (if exists) (mm) :	628-954 x 898 x 500
Dimensions of the packed product (HxWxD) (mm) :	580 x 650 x 970
Net weight (kg) :	19.663
Gross weight (kg) :	25.0

Optional accessories

- DHZ1223 : Chimney extension 1000 mm
- DHZ1233 : Chimney extension 1500 mm
- DHZ5345 : Recirculating kit
- DHZ5346 : Active carbon filter
- DSZ5201 : CleanAir active carbon filter spare part
- DSZ6240 : CleanAir Recirculation Kit
- DWZ0XX0J5 : Integrated CleanAir Recirculation Kit
- DWZ0XX0J5 : Integrated CleanAir Recirculation Kit
- DZZ0XX0P0 : CleanAir act.carbon filter regenerative
- HEZG9AS00S : Adapter



4 242005 086610



Serie | 6 Hoods

DWB97JP50

DWB97JP50 Brushed steel

Chimney hood

Box design

The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.

- Energy Efficiency Class: A (at a range of energy efficiency classes from A++ to E)
- Average Energy Consumption: 33.6 kWh/year
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A
- Grease Filtering Efficiency Class: B
- Noise min./max. Normal Level: 45/55 dB

Variant:

Design:

Operating and power:

Operating mode / operation

Power:

Environment and safety:

Comfort:

Measures:

Technical information:

- Chimney hood
- 90 cm wide
- Appliance colour: Brushed steel
- Suitable for ducted or re-circulated extraction
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Wall mounted hood
- Wall fixing system
- TouchControl for extractor speeds and light
- Electronic controls
- TouchControl with lightline
- 3 speeds plus 2 intensive via TouchControl
- Electronic controls via TouchControl with lightline
- TouchControl (3 speeds plus 2 intensive) with lightline
- 3 speeds plus 2 intensive
- Automatic revert setting, 6 minutes
- Automatic 10 minutes after running
- easy to clean Innerframe
- Light dimmer function
- SoftLight
- Efficient BLDC-technology
- 3 x 1,5W LED
- Light Intensity: 373 lux
- Colour Temperature: 3500 K
- Saturation indicator for metal and charcoal filter
- Stainless steel filter covers, dishwasher safe
- Metal grease filter, dishwasher safe
- Extraction rate according to EN 61591 \varnothing 15 cm:
max. Normal use 427 m³/h
Intensive 702 m³/h
- Extraction rate exhaust air according to EN 61591 max. 427 m³/h
- Maximum extraction rate exhaust air 427 m³/h according to EN 61591
- Extraction rate exhaust air according to EN 61591:
max. normal use 427 m³/h, intensive 702 m³/h
- Dimensions recirculating with CleanAir module (HxWxD):
689 x 898 x 500 mm - mounting with outer chimney
809-1139 x 898 x 500 mm - mounting with telescopic chimney
- Additional noise insulation
- Noise level according to EN 60704-3 und EN 60704-2-13 at max. normal use exhaust air: 55 dB(A) re 1 pW (42 dB(A) re 20 μ Pa sound pressure)
- Noise level according to EN 60704-3 und EN 60704-2-13 exhaust air:
Max. normal use: 55 dB(A) re 1 pW sound pressure: 42 dB(A)
Intensive: 66 dB(A) re 1 pW (53 dB(A) re 20 μ Pa sound pressure)
- Diameter pipe \varnothing 150 mm (\varnothing 120 mm enclosed)
- with one-way flap
- Max. extraction rate: 702 m³/h
- Extraction rate in recirculation mode:
Max. normal use: 324 m³/h
Intensive: 378 m³/h
- Noise levels in recirculation mode:



CMC
ELECTRIC



Serie | 6 Hoods

** In accordance with the EU-Regulation No 65/2014*

CMC
ELECTRIC





Serie | 6 Hoods

DWB97JP50

DWB97JP50 Brushed steel

Chimney hood

Box design

